

# PANTUM

The New Era for Printing

**P3300 Series**  
Monochrome Laser Printer

## Reduce your printing cost at utmost

Let the new Pantum P3300 series bring your business value with auto-duplex high speed printing for high working efficiency, low paper jam rate for fluent operation, and eco-friendly separate drum unit and toner cartridge to reduce your cost at utmost. It is ideally suited for users no matter from small business group or from large shared workgroup who require affordable running cost.



Silent printing mode to lower the noise and create a comfortable office environment



**Wifi One Step Installation and Direct Printing**



**Office document direct print from mobile devices**



**Low paper jam rate design for engine**



**High print speed**



**Convenient to print**



**Separate drum and toner**



# PANTUM

[WWW.PANTUM.COM](http://WWW.PANTUM.COM)

# KEY SPECIFICATIONS



## P3300 Series Monochrome Laser Printer

Model	P3300DN	:	P3300DW
<b>Printing</b>			
Print technology	Mono laser		
Print speed	33ppm(A4)/35ppm(Letter)		
First print out time	Less than 8.2 seconds		
Max. monthly volume	60000 pages		
Recommended monthly volume	750 to 3500 pages		
Processor speed	350 MHz		
Memory	256 MB		
Resolution(dpi)	1200x1200 dpi (Max)		
Printer language	PCL5e, PCL6, PS3, PDF		
Duplex mode	Auto		
Control panel	2Line LCD		
NFC print	No	:	Yes
Network print	Yes		
Wireless print	No	:	Yes

<b>Paper handling</b>			
Paper input tray	250 pages		
Multipurpose tray	1 pages		
Paper output tray	150 pages		
Media types	Plain, Thick, Transparency, Cardstock, Lable, Envelope		
Media sizes	A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2		
Media weight	Input tray: 60-105g/m <sup>2</sup> Multipurpose tray: 60-200g/m <sup>2</sup>		

<b>General</b>			
Dimensions (wxdxh)	354 x334x 232mm(13.9x 13.1x9.1in)		
Weight (without toner cartridge)	6.8kg (15lb)		
Operating temperature range	10-32 °C (50-95 °F)		
Operating humidity range	20% - 80% RH		
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%, +10%), 50/60Hz(±2Hz), 4.5A		
Noise	Printing: ≤52dB(A) Standby: ≤30dB(A)		
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2 W		
Operating system compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04);	:	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04); iOS 7.0 and above; Android 4.4 and above
Interface	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx	:	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n

<b>Supplies</b>			
Cartridge style	Separate drum and toner		
Starter cartridge capacity <sup>(1)</sup>	TL-410 (1500 pages)		
Cartridge and drum capacity <sup>(1)</sup>	Cartridge: TL-410 (1500 pages, Standard); TL-410H (3000 pages, High); TL-410X (6000 pages, Extra high) Drum: DL-410 (12000pages)		
Starter drum unit lifetime <sup>(1)</sup> <small>(Print with A4 paper page by page discontinuously)</small>	DL-410 (12000 pages)		

<b>What's in the box</b>			
Printer × 1/ 1500 Page Toner Cartridge × 1/ 12000 Page Drum unit × 1/ USB Interface Cable × 1/ Power Cord × 1/ CD-ROM × 1/ Quick Setup Guide × 1			

(1) Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience different results based on their environment and page coverage)  
Copyright ©2017 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.