



KONICA MINOLTA

TECHNOLOGY



AccurioPress 6120

MONOCHROME DIGITAL PRODUCTION PRESS / COPIER / SCANNER

120 ppm output for high-volume monochrome print production

Inline, closed loop quality management system

High-speed dual color scanning at 240 ipm

Job ticket and page editing from 15" touch-screen display for easy on-board press control

Color Centro and Hot Folder capabilities for job management and workflow

True 1,200 x 1,200 dpi resolution with enhanced screening technologies for sharpness

Duty cycle 2,500,000 — accepts media up to 350 gsm

Reliable air-suction paper feed option for smooth paper feeding

Professional feeding of coated media and envelopes

18,000-sheet maximum paper capacity with options

Humidifier option removes static, reduces paper curl

Saddle-stitched booklets with three-side trim and square-fold

Produce 600-page perfect bound books and up to 100-sheet stapling

Envelope print support with optional fuser

Innovative GBC punch unit with interchangeable die sets

Built-in print controller with PCL, PostScript, TIFF and PDF

Simitri[®] HD toner with Biomass to protect the environment

EPEAT Gold-certified — U.S. Energy Star compliant

AccurioPress 6120

MONOCHROME DIGITAL PRODUCTION PRESS / COPIER / SCANNER

Built to perform in high-volume environments, the AccurioPress 6120 sets a new standard in monochrome printing. Print/copy speeds up to 120 ppm reach new levels in efficiency, with high-volume monthly duty cycle of 2.5 million impressions, real-time automated density and registration adjustments maintain image stability over long press runs.

SYSTEM SPECIFICATIONS

Resolution	Print: 1,200 x 1,200 dpi Scan: 600 x 600 dpi
Paper weight	Standard: 40-300 gsm Opt: PF-710, PF-709 (middle tray) - 40-350 gsm
Auto duplex	40-300 gsm
Paper sizes (max.)	324 x 463 mm (12.76" x 18.23") Opt: PF-709 - 324 x 463 mm (12.76" x 18.23") PF-710 - 324 x 483 mm (12.76" x 19.02")
Paper sizes (min.)	182 x 139 mm (7.17" x 5.47") Opt: PF-709 - 95 x 139 mm (3.74" x 5.47") PF-710 - 95 x 133 mm (3.74" x 5.24")
Image loss (max.)	3.0 mm or less for top edge 2.0 mm or less for bottom edge 2.0 mm or less for right/left edges
Warm-up time	420 seconds or less
Paper input capacity	Standard: 3,000 sheets Max.: 18,000 sheets
Main unit dimensions (W x D x H)	39" x 35.8" x 57"
Main unit weight	813.5 lbs
Power requirements	208VAC to 240VAC, 20A, 60 Hz

PRODUCTIVITY

8.5" x 11" (max. per minute)	120 ppm
Monthly duty cycle (max.)	2,500,000 pages

CONTROLLER

Type	Embedded (network standard)
CPU	Intel i5-4570S 2.9 GHz
Memory	16 GB
HDD/SSD	HDD: 1-TB x2, SSD: 4 GB
Print-description language	PS/PS3 (PCL6), Adobe PostScript3 (PS3020), PDF v1.7, TIFF v6, PPM, v2.2, APP64.2 (with UK-217)
Printing method	TCR/IP (LPR, RAW socket), NetBEUI, IPP, WSD, Bonjour, SMB
Applicable OS	PCL, PS, PS Plug-in: Windows 7 [®] /8.1 [™] /10 [®] Windows Server 2008/2008R2/2012/2012R2/2016 Mac OS X 10.8/10.9/10.10/10.11/10.12
Interface	10/100/1000Base-T, USB3.0 host, USB2.0 device

² Including 64-bit versions.

SCANNER SPECIFICATIONS

Type	Full color
Scan speed (8.5" x 11")	Single-sided 120 ipm/duplex 240 ipm
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-HDD; Scan-to-FTP; Scan-to-SMB; Scan-to-Email; Scan-to-WebDAV; Scan-to-USB
Scan formats	TIFF, PDF, Encrypted PDF, PDF/A-1a, PDF/A-1b, Compact PDF, JPEG, XPS

COPIER SPECIFICATIONS

Gradations	256 gradations
First copy out¹	2.8 sec. or less
Continuous print speed²	120 pages/min (letter landscape)
Magnification	25-400% in 0.1% steps

¹ When letter landscape original is scanned on the platen (zoom 100%, Tray-1).

² Print speed may vary depending on paper type.

OPTIONS

CR-101	Creaser unit for SD-513	MK-732	Post-inserter mount kit for FS-532
EF-105	Envelope fuser	MK-737	Mount kit for third-party products
FA-503	PFU adjustment kit	OT-510	Open stacker
FD-503	Multi-fold punch unit	PB-503	Perfect binder
FD-504	Squeeze folding unit for SD-513	PF-709	Friction paper feed unit w/air assist
FS-532	100-sheet staple finisher	PP-701	Pre-printed paper kit for PF-709
FS-532 PK/SD	100-sheet staple finisher with PK and SD-510-522	PF-710	Vacuum paper feed unit
Punch G2	GBC advanced multi-punching unit	PI-502	Post inserter for FS-532
GP-501	GBC multi-hole punch unit	PK-522	2/3-hole punch for FS-532
GP-502	GBC in-line ring binding unit	RH-101	Removable HDD kit
HD-523	Inner HDD kit	RU-510	Relay unit for GP-501
HM-103	Humidification unit for RU-518	RU-518	Relay unit for de-curling
HT-506	Dehumidification heating unit for PF-710	SD-506	Booklet making unit
IQ-501	Intelligent quality optimizer	SD-510	Saddle stitch kit for FS-532
LC-501	Cart for LS-506	SD-513	Saddle stitch unit
LS-506	Stacking unit	SD-513/F	Saddle stitcher front
		TU-503	Trimmer unit for SD-513



For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA and the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com



Item # - AP6120S
2/2018-C